



**Product Code**

# VR207


**Product Description**

An architectural recessed downlight with a diffused structure, providing uniform and soft light distribution. It is used for general lighting in residential spaces, offices, and shared areas where visual comfort is essential.


**Specifications**

Inch	2"	3"	4"	5"	6"	8"
Watt	8W	12W	15W	20W	25W	40W
Current	200	250	350	500	700	900
Luminous Flux	980	1320	1750	2200	3750	4400
CRI	80	80	80	80	80	80
IP Class	20-44	20-44	20-44	20-44	20-44	20-44
Diameter (A)	108mm	128mm	150mm	180mm	200mm	240mm
Cut Out (B)	90mm	105mm	130mm	160mm	180mm	210mm
Depth (C)	65mm	55mm	55mm	55mm	55mm	58mm

C




A



Light Angle	36°
Color Temperature	2700K / 3000K / 4000K / 6500K
Case Color	RAL (Colors)
COB LED	<b>TRIDONIC SAMSUNG OSRAM</b>
DRIVER	<b>TRIDONIC EAGLE RISE OSRAM PHILIPS</b>

Light Distribution



Aluminium Injection Body	Compatible Driver with DALI
Electrostatic Powder Coated	Compatible with Emergency Kit
Heat Resistant Glass	